

HYBRID EXTRICATION



Featuring **F**it **F**orm **F**unction
Technology



EN 388



4343

FEATURES:

ResqLoc Grip System

CE Certified Puncture and Cut Protection

TPR Impact Protection on Top of Hand and Full Length of Fingers

High Visibility Dorsal Area

Supercuff™ Technology for Full Range of Motion

Hi-Vis



337-08	: S
337-09	: M
337-10	: L
337-11	: XL
337-12	: XXL
337-13	: XXXL



Distributed By:

Ringers Gloves • 335 Science Dr. • Moorpark, CA 93021
P:805.517.1061 • F:805.517.1071 • www.ringersgloves.com

EXTRICATION HYBRID



ABRASION :

Performance Levels	0	1	2	3	4	5
Abrasion Resistance	< 100	100	500	2000	8000	---
Extrication Abrasion Resistance						
Lowest value of four tests:				> 8000		
Performance Level:				4		

BLADE CUT :

Performance Levels	0	1	2	3	4	5
Blade Cut Resistance	< 1.2	1.2	2.5	5.0	10.0	20.0
Extrication Blade Cut Resistance						
Sequence			Test 1		Test 2	
1			6.1		4.8	
2			5.9		6.4	
3			8.0		7.0	
4			7.1		7.2	
5			7.3		7.4	
Average:			6.9		6.6	
Lowest Average Value:			6.6		Between 2.5 and 5.0 = 2	
Performance Level:			3		Between 5.0 and 10.0 = 3	

TEAR :

Performance Levels	0	1	2	3	4	5
Tear Resistance	< 10	10	25	50	75	---
Extrication Tear Resistance						
Lowest value of four tests:			77		Between 50 and 75 = 3	
Performance Level:			4		Over 75 = 4	

PUNCTURE :

Performance Levels	0	1	2	3	4	5
Puncture Resistance	< 20	20	60	100	150	---
Extrication Puncture Resistance						
Lowest value of four tests:			117		Between 60 and 100 = 2	
Performance Level:			3		Between 100 and 150 = 3	

DEXTERITY :

Performance Levels	0	1	2	3	4	5
Dexterity	---	11.0	9.5	8.0	6.5	5.0
Extrication Dexterity						
Highest value of four tests:			5.0		5.0 = 5	
Performance Level:			5			

EN 388

4343

Hi-Vis	
337-08	:S
337-09	:M
337-10	:L
337-11	:XL
337-12	:XXL
337-13	:XXXL

OVERALL:

Dexterity	5	Out of 5
Abrasion Resistance	4	Out of 4
Blade Cut Resistance	3	Out of 5
Tear Resistance	4	Out of 4
Puncture Resistance	3	Out of 4