



GENERAL FIRE

800-541-4218



3904 - 4004 E Trent Spokane, WA. 99202
YOUR SINGLE SOURCE FOR SALES & SERVICE SINCE 1957

STATION FOOTWEAR

MODEL 6026

STATION FOOTWEAR 804-6026



6" Quick Release Station Boot Safety Toe

75 -Safety Toe Class I/75 footwear retains a .500 inch (1/2 inch) for men's and .468 inch (15/32 inch) for women's or greater clearance after a nominal impact of 75 foot-pounds (101.7J), i.e., a 50 pound weight dropped from 18 inches reaching 117.9 ± 2.4 inches per second velocity at impact. Compression: Class C/75 footwear retains a .500 inch (1/2 inch) after compression of 2500 lbs. (11,121 N) or greater. Meets ASTM 2413-05 M/I/75/C/75 ratings.

EH -Electrical Hazard Protective footwear constructed or manufactured with electric shock resisting soles and heels capable of withstanding an application of 14,000 volts (root mean square (RMS) value) at 60 Hz for 1 minute with no current flow or leakage current in excess of 3.0 milliamperes under dry conditions.

ESR -Electric Shock Resistance Electric Shock Resistance

NM -Non-Marking Does not leave surface residue when tested according to MIL-S-22777 paragraph 4.5.1.

UPPER: Black Full Grain Leather

CONSTRUCTION: Direct Injection

OUTSOLE: Translucent TPU (Thermo Plastic Urethane)

LINING: Non-Woven Nylon

INSOLE: Removable Polyurethane

MIDSOLE: Polyurethane

SHANK: Plastic

SPECIAL FEATURES: ASTM F 2413-05 M/I/75/C/75 Steel Toe. Electrical Hazard. Tested For and Meets CAN/CSA-Z195 18,000 Volts Electrical Shock Resistance Standard.

Quick Release Elastic Gore. Pull Straps

M 7 - 12 , 13, 14

W 7 - 12 , 13, 14