

GENERAL FIRE APPARATUS, INC.

MAIN WAREHOUSE | FABRICATION PLANT SERVICE CENTER | 4004 E. Trent Ave., Spokane, WA 99202
 P: (509) 535-4255 | F: (509) 534-8529 | TF: 1-800-541-4218 | www.generalfire.com

GENERAL FIRE "CHIEF SERIES" OF APPARATUS

ADAMS COUNTY FPD #2

DON KLEMMER FIRE CHIEF
 LIND, WASHINGTON

[CLICK HERE TO VIEW DRAWING](#)



Deutz fire pump engine powering Waterous CP-2 & electric primer & mech seals	Spring door hold opens, polished drip moldings & painted cabinet interiors
Waterous CP-2 pump performance 300 GPM at 150 PSI 60 GPM at 400 PSI	2 single door triangular upper storage compartments in action center
Two control panels 1 in the cab and 1 at the rear street level & water & foam gauges	2 compartments mounted in front of the rear wheels with double doors
Akron HD valves with TS control handles, 2 rear preconnects & 2 front turret positions	10' & 6' with Dee handle pike poles mounted on heat shield & scuff plates
Gated front corner turret positions with padded railed & 2 Akron Turbojet nozzles	Hard bore suction hose, aluminum mounting brackets and strainers
Rear 2 1/2" gated suction & discharge, 3" tank to pump & Y strainer & cleanout fitting	Action area work lights, battery disconnect in cab entrance driver side
HyPro 1600 series injection foam system, 20 gallon A Class foam cell & level indicator	Code 3 3692 light and siren controls, LED lightbar and emergency lighting
200"x1" rear electric booster reel with 2 fairlead roller and guides & Akron nozzle	12 volt left and right side scene lighting mounted on upper heat shield
Single rear mounted direct tank fill, Akron valve with 2" camlock fitting cap and chain	2009 IH 7400 4x4 2 door chassis with 14k front & 23k rear axle ratings
Low Profile 1200 gallon stainless steel water tank with 20 gallon integral foam cell	IH 330 HP MaxxForce 9 diesel with 950 ft lbs torque @1200 rpm's
Thermo Coated upper tank work space with WAC gate, heat shields & padded handrails	National Air ride drivers seat & two person passenger seat with storage
34" Side heat shields, 4" toe kick and 5" high hand railing with foam padded enclosure	2-Rechargeable Streamlight flashlights, 10# ABC and wheel chock bracket
Double paneled aluminum doors & slam latch stainless steel D ring door handles	24 unit First Aid kit, 400' 1 1/2" double jacket hose and Akron nozzles



