

GENERAL FIRE APPARATUS

509-535-4255, TOLL FREE 800-541-4218
www.generalfire.com



CITY OF IDAHO FALLS FIRE DEPT

Idaho Falls, Idaho

[CLICK HERE TO VIEW DRAWING](#)

[CLICK BELOW TO VIEW ADDITIONAL DETAILS](#)



[KUSSMAUL AUTO EJECTOR](#)



[SecureAll™ SCBA LOCKING SYSTEM](#)



[EZ CLIMB LADDER](#)



[AKRON DISCHARGE VALVES](#)



[WELDON LIGHTS](#)



[VULCAN HAND LIGHTS](#)

Rosenbauer/Spartan Metro Star Custom Chassis, 18k front & 24k rear axle rating
Left & right exterior & interior access EMS compartment between cab doors
Cummins ISC 8.3 380 HP 1050 foot pounds of torque at 1400 RPM
Polished aluminum wheels, lug nut & hub covers, Hadley brand E-Tone air horns
Officer's seat back is a SecureAll™ SCBA locking system & H.O. Bostrom seat
Floor mounted storage in crew cab with 4 access doors 2 front & 2 on the ends
Cummins Quick Check QC5100 engine & Allison's DOC diagnostic software kit
Portable pump plumbed into discharge manifold, Waterous 1500 GPM pump
3" tank to pump & 2" tank refill, TFT intake relief valve, 2-2 1/2" gated intakes
5-2 1/2" gated discharges, chrome droops, line gauges & chrome cap with chains
1" x 150' electric booster reel, hose, nozzle cup, stainless roller/guide assembly
Fire Research TankVision foam tank indicator & low level indicator back-up
Slide out bottom pump enclosure, Noshok intake & discharge gauges
2-250" adjustable aluminum hosebed divider & vinyl hosebed cover & end flaps
ROM aluminum roll-up doors, adjustable aluminum trays, incandescent lighting
Dual end electric/hydraulic ladder rack mounted on passenger side
EZ Climb access ladder mounted on left rear for easy upper access to the body
Kussmaul Pump Plus 1200 battery charger and air compressor system with gauge
2-12 volt telescoping work lights, 2 Vulcan LED rechargeable hand lanterns
Opticom traffic light emitter system, Akron discharge valves & Weldon lights

10" raised roof 2 tone red/white 3/16" aluminum custom fire service chassis cab
Class One Vehicle Data Recorder system, 5052-H32 Marine Grade engine tunnel
Allison Gen IV-E EVS automatic transmission with touch pad operations in cab
Driver's seat with air suspension, two (2) way adjustable contoured & head rest
2 forward facing outboard crew seats with SecureAll SCBA locking system
4-18.00 inch knurled, anti-slip, one-piece exterior handle behind each cab door
6 Zico UHH-1 in cab helmet holder, Waterous portable fire pump in dunnage
6" butterfly valve on suction inlet, InControl pressure governor, pump anodes
2-1 3/4" crosslay, aluminum bed cover with vinyl end flaps & roller guides
3" TFT 1250 GPM deck monitor, stack tips, 1250 master stream & tele waterway
Foam Pro 1600 injection foam system & 20 gallon integral Poly foam cell
Black thermal coated bolted on side control panels with upper hinged access
Fire Research Tank Vision LED tank level gauge, 500 gallon Poly water tank
Rosenbauer 3/16" aluminum body & hot dipped galvanized body subframe
Roll-out heavy duty trays, 3/16" aluminum tool mount board space & bolted
Ladder set included, pike pole tubes & folding ladder mounts on body
SCBA cylinder compartment mounted in rear wheel area left & right side
Super Auto-Eject 20-amp automatic disconnect on the 110 volt shoreline
Federal Q2 mechanical siren with officer & driver foot switch in cab
1" x 4" x 1" Scotchlite trim & rear chevron, 35' 3 extension & 10' folder ladders