


GENERAL FIRE APPARATUS, INC.

MAIN WAREHOUSE | FABRICATION PLANT SERVICE CENTER | 4004 E. Trent Ave., Spokane, WA 99202
 P: (509) 535-4255 | F: (509) 534-8529 | TF: 1-800-541-4218 | www.generalfire.com



"X" Body Low Profile Engine



B & S 26 hp Diesel Pump Engine	Waterous E511 Fire Pump	Pressure of 100 GPM at 190 PSI
Volumes of 300 GPM at 50 PSI	Akron Quarter Turn Ball Valves	Rotary Vane Electric Priming System
1-1" & 2-1 1/2" Rear Discharge	2 Rear Preconnected Storage Trays	Rear Overboard Suction
2 - 1 1/2" Rear Preconnects	Hy-Pro 2001 Foam System	12 Gallon Poly Clear Foam Cell
2 1/2" Rear Direct Tank/Hydrant Fill	Rear Center Access & Handrails	500 Gallons Stainless Steel Tank
Right Rear Pump Control Panels	Double Panned Aluminum Doors	Left & Right Upper & Lower Storage
Aluminum High Side Compartments	Full Height Rear Side Compartments	Rear Suction Hose Compartment
Stainless Steel Lower Body	Extruded Aluminum Upper Body	Class One Water Level Indicators
Seven Adjustable Unistrut Shelves	SCBA Mounting Brackets	4" White Scotchlite "Z" Stripping
Automatic Lighted Compartments	Code 3 Halogens Emergency Lights	LED / DOT Side & Rear Lighting
D/C Tele & Scene Lighting	Commercial Chassis Runningboards	Stainless Steel Wheel Covers
PPG Concept II & Morton Coatings	Warn 15K Recessed Bumper Winch	Limited Slip Rear Axle
4 Door Super Cab With 60" CA	Diesel Power Stroke Engine	Automatic Transmission
Four Wheel Drive	17,500 GVWR	Ford Automatic High Idle
Dual 115 Amp Alternators	Dual Batteries	AA-F-Series Custom Dash Module





