



GENERAL FIRE

800-541-4218



3904 - 4004 E Trent Spokane, WA. 99202
YOUR SINGLE SOURCE FOR SALES & SERVICE SINCE 1957

DESCRIPTION: Rear Discharge & Recessed Rear Step

PLANT: Rosenbauer

SPECIFICATION: Two crosslay hosebeds shall be provided, each designed to carry 200 feet of 1-3/4" double jacket fire hose. The crosslay hosebeds shall be located in the rear bumper. The top and sides shall be fabricated of polished 3/16" aluminum treadplate. There shall be a three piece design cover provided. The two outer sections shall be aluminum, hinged style covers with stainless steel hinge and two hold-down latches. The center section below the dump valve assembly shall be a removable style vinyl cover.

The crosslay discharge(s) shall be plumbed using rigid pipe or flexible high-pressure hose coupled with stainless steel fittings. The crosslay(s) shall be provided with 2" brass valve, and a 2" 90 degree swivel adapter (one per side) with 1-1/2" NST male outlet thread.

In order to maximize ground clearance, the crosslay assemblies are to be raised above tailboard but below the swivel dump to minimize the amount extending below the tailboard. The width shall be approximately the same as the hose bed width to allow a step area on either side of the tailboard, beside the crosslays.



800-541-4218



LOCAL PHONE 509-535-4255

FAX 509-534-8529

EMAIL GFABELL@GENERALFIRE.COM

WEB SITE WWW.GENERALFIRE.COM