

# GENERAL FIRE APPARATUS, INC.

MAIN WAREHOUSE | FABRICATION PLANT SERVICE CENTER | 4004 E. Trent Ave., Spokane, WA 99202  
P: (509) 535-4255 | F: (509) 534-8529 | TF: 1-800-541-4218 | www.generalfire.com



# SPOT LIGHT

## SLIDE-OUT HOSE LOADING PLATFORM

DESCRIPTION: Slide-Out Hose Loading Platform

PLANT: Rosenbauer

SPECIFICATION: There shall be a manual slide-out hose loading platform rated for 750 pounds located above the rear wheels on the officer side of the truck to aid in re-loading the hose bed. The platform shall be approximately 75" wide and slide out of the body approximately 22". There shall be a retractable ladder that is stored in the floor of the platform. When the hose loading platform is in the deployed position, the ladder shall pull out of the floor at the rear of the platform and extend down to ground level for an easy egress to the platform. There shall be a continuous hand rail attached to the outer face of the platform that runs up the rear and continues along the top to the front. An electric actuated lock shall be provided to lock the platform in both the stowed and deployed positions. The lock shall be activated by a rocker switch located in the R1 compartment. Two On-Scene Solution LED step lights shall be provided and located above the platform illuminating the platform. The platform's exterior surface of the platform shall be painted to match the body. When not in use, the platform shall fit flush with the body to prevent the platform from being damaged. The platform shall be wired into the "Do Not Move Apparatus" light and there shall be two LED lights located on the lower outer face of the platform that flash while the platform is in the deployed position.

